

AGS COMPANY

P.O. Box 729 Muskegon, MI 49443 231-733-2101 Fax: 231-733-1784 info@agscompany.com



DIELECTRIC Connector Protector

- **DESCRIPTION:** The material covered by this specification is a non-petroleum, synthetic, high temperature, hydrophobic dielectric grease. CONNECTOR PROTECTOR is formulated to stay put, locking out the moisture which could lead to corrosion of sensitive electrical components. CONNECTOR PROTECTOR will not harm the rubber or plastic components used in manufactruig electrical sockets or connectors.
- **APPLICATION:** Protects and seals out moisture when used on cars, trucks, marine or outdoor equipment; plugs, sockets, connectors, bulbs and many other applications where a good clean electrical connection is needed.

 Packaging:
 CONNECTOR PROTECTOR is available in various sizes. Call factory for availability of larger industrial size containers

 CP-1
 4gm pouch

 CP-1QS
 4gm pouch Quick Strip

 CPK-1K
 4gm pouch carded

Properties:	Physical Form	White Grease (gel)
	Specific Gravity	1.11
	Density, lb/gal	9.26
	NLGI, grade	2
	Flash Point, base oils (C.O.C., ⁰ F)	>400
	Operating temperature, ⁰ F	>600